

CABLE CONTROLLING BRACKET



Part No.	Description	Weight (lb/kg)
16-290	Holds 1/2": 65 ft-lb	11.5 / 5.22
16-291	Holds 5/8": 95 ft-lb	11.5 / 5.22
16-292	Holds 3/8": 45 ft-lb	6.5 / 2.94

DESCRIPTION

Wurtec **Cable Controlling Brackets** are simple and economical devices designed to facilitate the simultaneous reeving of up to 6 ropes. They are equipped with 6 cable clamps to securely grip the ends of wire rope, and 6 mounting holes to adapt to a variety of uses and conditions. It will keep ropes orderly and prevent rotation as they are being installed.

These devices are not intended to clamp ropes anywhere that is intended to be "live". It is only for use on the ends of ropes that will be later cut off, or beyond the wedge clamp as part of the "tail".

These devices are equipped with cable saddles, similar to a "Crosby" clip. Instead of U-bolts, the saddles are attached to hex bolts welded to the base plate, facilitating installation.

INSTRUCTIONS

To install ropes: loosen the saddle just enough to slide the rope between the saddle and the base plate. Then torque the (2) nuts as specified below in 10 ft/lb increments, alternating between each nut until the specified torque is reached. Repeat for each rope.

3/8": 45 ft-lbs

1/2": 65 ft-lbs

5/8": 95 ft-lbs

Connect the device to your hoisting rope or cabling sled to reeve up to (6) ropes at once while keeping them in order and preventing rotation.

After each use, check the base plate for cracking especially at mounting holes. Check the saddles for wear, and the saddle bolt welds for cracks.