



60-052
Aluminum Rope Clamp



60-10040479
Spanner Wrench

PRODUCT DESCRIPTION

Wurtec **Aluminum Rope Clamps** provide a secure and dependable method for joining two wire ropes or creating a temporary lifting point during elevator installation, maintenance, and modernization. Precision-machined with grip-enhancing internal grooves, the clamps deliver increased holding strength while helping maintain secure rope engagement during lifting and rope shortening operations.

Available in multiple sizes to accommodate a wide range of rope diameters, the clamps are designed for reliable performance in demanding field applications. Each clamp is tightened to 96 ft-lbs. for proper clamping force, and the optional Wurtec Spanner Wrench is recommended to help technicians achieve the required torque in confined installation environments.

KEY FEATURES

- Securely joins two wire ropes or creates a lifting point.
- Grip-enhancing internal grooves increase holding capacity.
- Available for a wide range of wire rope sizes.
- Designed for wire rope shortening applications.
- Tightens to a specified 96 ft-lbs. torque.
- Available in multiple load capacities.
- Compatible with the Wurtec Spanner Wrench for easier installation.

SPECIFICATIONS_60-05X

ALUMINUM ROPE CLAMPS

ORDERING INFORMATION

Part No	Rope Size (in)	Rope Size (mm)	Capacity (lbs kg)	Torque (ft-lb Nm)	Weight (lbs kg)	Rope Spacing In- Clamp (in mm)	Rope Spacing Between Clamps (in mm)
60-052	7/16	11	1500 680	96 30	6.9 3.1	1.19 28.9	3.06 77.7
60-053	7/8	22	2000 907	96 30	7.6 3.5	1.67 42.4	3.58 90.9
60-054	3/8	9-10	1500 680	96 30	6.9 3.1	1.13 28.7	3.06 77.7
60-055	1/2-9/16	12-14	2000 907	96 30	7.0 3.2	1.33 33.8	3.04 77.2
60-056	5/16	7-8	1250 567	96 30	6.7 3.0	1.06 26.9	2.94 74.7
60-057	3/4	18-20	2000 907	96 30	7.5 3.4	1.50 38.1	3.50 88.9
60-058	5/8-11/16	15-17	2000 907	96 30	7.2 3.3	1.46 37.1	3.18 80.8

SPECIFICATIONS_60-05X