



3218-010-KIT
8" x 8" Access Door

PRODUCT DESCRIPTION

These universal fire-rated access doors with mortise locks are designed to install easily and work perfectly in any wall or ceiling, including drywall, masonry (with masonry anchors factory installed), and suspended acoustical ceilings.

KEY FEATURES

- Fire rated. Carries both the UL and CUL 1-1/2 hour, Class B fire rating as well as the Warnock Hersey Label for 3-hour noncombustible floor/ceiling systems.
- UL (CUL) certified. 250° temperature rise for true fire safety. Without insulation, the temperature on the protected side of an access door exceeds 600° F, endangering people and causing spontaneous ignition of anything near the access door. Universal fire-rated doors are insulated with super-efficient insulation to limit temperature after 30 minutes to only 250°. This temperature rise is the best in the business.
- Reduced sound transmission thanks to the sandwich-type insulated door panel.
- Choice of finishes. Prime-painted for finishing to match the wall, or attractive stainless steel.

SPECIFICATIONS_3218-XXX-KIT

ORDERING INFORMATION

Part No.	Dimensions
3218-010-KIT	8" x 8"
3218-012-KIT	12" x 12"
3218-014-KIT	14" x 14"
3218-016-KIT	16" x 16"
3218-018-KIT	18" x 18"
3218-020-KIT	12" x 24"
3218-022-KIT	22" x 30"
3218-023-KIT	24" x 30"
3218-024-KIT	24" x 24"
3218-027-KIT	22" x 36"
3218-028-KIT	24" x 36"
3218-030-KIT	30" x 30"

*Kits include key sets