

TOP-OF-CAR HANDRAILS

Product Description



18-400



18-400-R

#18-400-R shares all the same great features of the other handrails, but is octagonal, making it an easy fit for round car tops ranging from 74" to 120" in diameter.

The Wurtec top-of-car handrail has a fully adjustable, telescopic tubing design that adapts to both existing cab configurations and new installations. It is fast and easy to install - no drilling required.

The top-of-car handrail mounts to Unistrut channel (not provided) on the top of the elevator canopy. The kit comes complete with all necessary assembly hardware and kickplates. All material is galvanized for corrosion prevention.

Key Features

- Fully adjustable (telescopic) design
- Fast and easy to install; mounts to the edge of the canopy
- Assembly hardware included
- Kickplate provided for field adaptation
- Made from galvanized 16-gauge tubing
- Available in both front-opening only and front- and rear-opening configurations
- Kickplate provided for field adaptation
- Custom sizes available upon request
- Complies with ASME A7.1-2016, Section 2.10.2 and 2.14.1.17

Part No.	Configuration	Width	Depth
18-400	Front Opening	66" - 96"	46" - 70"
18-400-R	Front Opening	Ø 74" - 120"	66-
18-410	Front Opening	46" - 70"	66" - 110"
18-420	Front & Rear Opening	≤ 72"	66" - 110"
18-430	Front & Rear Opening	≤ 96"	46" - 70"
18-440	Front Opening	66" - 96"	66" - 96"
18-450	Front Opening	66" - 96"	66" - 110"