



10-520



10-520-KIT



10-520-KIT-C

PRODUCT DESCRIPTION

The Wurtec Oil Evac Unit is designed to quickly and efficiently evacuate hydraulic fluid from hydraulic elevator jacks during installation, maintenance, and repair. Powered by a standard air compressor, the unit connects to Victaulic® fittings and uses compressed air to transfer hydraulic fluid, helping technicians perform clean, efficient fluid removal with minimal downtime. Available as a standalone unit or complete kit, the Oil Evac Unit can be configured with hydraulic hoses, an air hose, and a portable air compressor to meet a variety of field service requirements. Its modular design provides a practical solution for both shop and on-site hydraulic elevator service operations.

KEY FEATURES

- Quickly evacuates hydraulic fluid from elevator jacks.
- Connects directly to Victaulic® fittings.
- Operates using standard compressed air.
- Powered by a 60 PSI air supply.
- Available as a standalone unit or complete kit.
- Optional kits include hydraulic hoses and air hose.
- Complete kit available with portable air compressor.
- Designed for hydraulic elevator installation and maintenance.

Part Number	Description
10-520	Oil Evac Unit w/ Hydraulic Hose
10-520-KIT	Oil Evac Unit w/ 3 Lengths of Hydraulic Hose & 1 Length of Air Hose
10-520-KIT-C	Oil Evac Unit w/ 3 Lengths of Hydraulic Hose, 1 Air Hose, & 1 DEWALT® Air Compressor (4.5 Gallon, 200 PSI, 5.2 SCFM @ 90 PSI, Vertical Stand w/ 10" Non-Flat Foam Tires)

SPECIFICATIONS_10-520