

PEARLWEAVE® SAFETY NETTING

Part No.
PEARL-S048F
PearlWeave®, Standard-Grade, Fluorescent Red



PearlWeave® Safety Netting

PearlWeave® is the state of the art in workplace safety netting with a wide range of elevator industry applications. It is lightweight, tear-resistant, and reusable. Pricing per roll.

Key Features

- Fire-retardant / self-extinguishing
- Lightweight / flexible
- Non-conductive
- Tear-resistant
- Reusable

Elevator Industry Applications

- Dividing the shaft in multi-car hoistways
- Separating adjacent pit areas during service
- Counterweight compensation cable guarding
- Securing entrance openings
- Re-roping jobs

Part No.	Description	Stock Sizes	Mesh Size	Wt. per Roll	Lateral Force	Breaking Strength	Bursting Strength
PEARL-S048F	Standard-Grade Fluor. Red	48" x 150'	3/16"	15 lbs	250 lb	Warp: 40 lbs/in Fill: 45 lbs/in	60 PSI
PEARL-S102F	Standard-Grade Black	102" x 150'	3/16"	30 lbs	n/a	-	60 PSI
PEARL-048F	Premium-Grade Fluor. Orange	48" x 150'	3/16"	26 lbs	540 lb	80 lb/in	125 PSI
PEARL-102F	Premium-Grade Black	102" x 150'	1/8"	62 lbs	n/a	95 lb/in	150 PSI



Part No. 2H4
Beam Clip for PearlWeave®

Beam Clip

This spring-loaded **beam clip** is a quick and easy solution for hanging PearlWeave™ as a safety barrier. Just choose the right size for your flange thickness and fasten it to the beam, fixing the PearlWeave® in its grip.

Part No.	Flange Thickness	Static Load Limit	Weight
2H4	3/32" - 9/64"	160 lbs	8 lbs
4H24	1/8" - 1/4"	200 lbs	8 lbs
4H58	5/16" - 1/2"	200 lbs	8 lbs
4H912	9/16" - 3/4"	200 lbs	8 lbs