

ROEBLING CLAMPS



Product Description

Wurtec's **Roebling clamps** are a lightweight, portable alternative to traditional wire rope clamps.

These clamps provide a safe and efficient method for securing wire ropes, with a maximum working load of 600 lbs. per rope.

The spiral ridge design cast into the grooves of the clamp firmly grips wire ropes and prevents slippage, while the non-symmetrical hole pattern prevents incorrect assembly of the clamp.

Key Features

- Lightweight and portable
- 600 lbs. maximum safe working load per rope
- Spiral ridge design to prevent slippage
- Non-symmetrical hole pattern to prevent incorrect assembly
- Now available in metric sizes

⚠ WARNING

Inspect hardware for defects / deformation before use.

Part No.	Rope Size (in • mm)	Torque (ft-lbs • Nm)	Weight (lbs • kg)	Rope Spacing in Clamp (in • mm)	Rope Spacing between Clamps (in • mm)
60-251	5/16 • 7-8	80 • 108.5	3.0 • 1.4	1.00 • 25.4	1.01 • 25.7
60-252	3/8 • 9-10	80 • 108.5	3.5 • 1.6	1.00 • 25.4	1.01 • 25.7
60-253	7/16 • 11	80 • 108.5	4.3 • 2.0	1.00 • 25.4	1.01 • 25.7
60-254	1/2 - 9/16 • 12-14	80 • 108.5	4.3 • 2.0	1.03 • 26.2	1.00 • 25.4
60-255	5/8 - 11/16 • 15-17	80 • 108.5	4.8 • 2.2	1.24 • 31.5	1.10 • 27.9
60-256	3/4 • 18-20	80 • 108.5	5.0 • 2.3	1.32 • 33.5	1.09 • 27.7
60-257	7/8 • 22	80 • 108.5	7.3 • 3.3	1.43 • 36.3	1.56 • 39.6