

SHORTENING CLAMP



Product Description

The Wurtec rope shortening clamp allows the user to lift the elevator car by clamping onto the hoist ropes directly above the hitch plate.

Once the shortening clamp is in place, a hoist can be attached between it and the crosshead.

Slack can then be created in the hoist ropes, allowing for easy shortening of the rope at the hitch plate.

Each rope is gripped by (2) cast clamps, which have spiral edges in one groove.

WARNING

To prevent the cable from slipping, be sure the shortening clamp is positioned with serrated ridges on each rope.

part no.	no. of ropes	rope size (in)	rope size (mm)	capacity (lbs · kg)	torque (ft·lbs)
16-278	6	3/4	18-20	8000 · 3628	50
16-279	6	5/16	7-8	8000 · 3628	50
16-280	6	1/2	12-14	8000 · 3628	50
16-281	6	5/8-11/16	15-17	8000 · 3628	50
16-282	6	7/16	11	8000 · 3628	50
16-283	6	3/8	9-10	8000 · 3628	50
16-284	8	5/16	7-8	10000 · 4535	50
16-285	8	1/2-9/16	12-14	10000 · 4535	50
16-286	8	5/8-11/16	15-17	10000 · 4535	50
16-287	8	7/16	11	10000 · 4535	50
16-288	8	3/8	9-10	10000 · 4535	50
16-289	8	3/4	18-20	10000 · 4535	50
16-298	10	3/8	9-10	10000 · 4535	50
16-299	10	1/2-9/16	12-14	10000 · 4535	50